

C语言函数大全(w开头) PDF转换可能丢失图片或格式，建议
阅读原文

https://www.100test.com/kao_ti2020/135/2021_2022_C_E8_AF_AD_E8_A8_80_E5_87_BD_c97_135172.htm 函数名: wherex 功能: 返回窗口内水平光标位置 用法: int wherex(void). 程序例: #include int main(void) { clrscr(). gotoxy(10,10). cprintf("Current location is X: %d Y: %d\r\n", wherex(), wherey()). getch(). return 0. } 函数名: wherey 功能: 返回窗口内垂直光标位置 用法: int wherey(void). 程序例: #include int main(void) { clrscr(). gotoxy(10,10). cprintf("Current location is X: %d Y: %d\r\n", wherex(), wherey()). getch(). return 0. } 函数名: window 功能: 定义活动文本模式窗口 用法: void window(int left, int top, int right, int bottom). 程序例: #include int main(void) { window(10,10,40,11). textcolor(BLACK). textbackground(WHITE). cprintf("This is a test\r\n"). return 0. } 函数名: write 功能: 写到一文件中 用法: int write(int handel, void *buf, int nbyte). 程序例: #include #include #include #include #include #include int main(void) { int handle. char string[40]. int length, res. /* Create a file named "TEST. \$\$\$" in the current directory and write a string to it. If "TEST. \$\$\$" already exists, it will be overwritten. */ if ((handle = open("TEST. \$\$\$", O_WRONLY | O_CREAT | O_TRUNC, S_IREAD | S_IWRITE)) == -1) { printf("Error opening file.\n"). exit(1). } strcpy(string, "Hello, world!\n"). length = strlen(string). if ((res = write(handle, string, length)) != length) { printf("Error writing to the file.\n"). exit(1). } printf("Wrote %d bytes to the file.\n", res). close(handle). return 0. }

```
struct xfc { char xfc_flag. /* Contains 0xff to indicate xfc */ char
xfc_resv[5]. /* Reserved for DOS */ char xfc_attr. /* Search
attribute */ struct fcb xfc_fcb. /* The standard fcb */ }. 100Test 下
载频道开通，各类考试题目直接下载。详细请访问
www.100test.com
```