

## C语言函数大全(s开头)(1) PDF转换可能丢失图片或格式，建议阅读原文

[https://www.100test.com/kao\\_ti2020/135/2021\\_2022\\_C\\_E8\\_AF\\_AD\\_E8\\_A8\\_80\\_E5\\_87\\_BD\\_c97\\_135188.htm](https://www.100test.com/kao_ti2020/135/2021_2022_C_E8_AF_AD_E8_A8_80_E5_87_BD_c97_135188.htm) 函数名: sbrk 功能: 改变数据段空间位置 用法: char \*sbrk(int incr). 程序例: #include

```
#include int main(void) { printf("Changing allocation with sbrk()\n"). printf("Before sbrk() call: %lu bytes free\n", (unsigned long) coreleft()). sbrk(1000). printf(" After sbrk() call: %lu bytes free\n", (unsigned long) coreleft()). return 0. } 函数名: scanf 功能: 执行格式化输入 用法: int scanf(char *format[,argument,...]). 程序例: #include #include int main(void) { char label[20]. char name[20]. int entries = 0. int loop, age. double salary. struct Entry_struct { char name[20]. int age. float salary. } entry[20]. /* Input a label as a string of characters restricting to 20 characters */ printf("\n\nPlease enter a label for the chart: "). scanf(" s", label). fflush(stdin). /* flush the input stream in case of bad input */ /* Input number of entries as an integer */ printf("How many entries will there be? (less than 20) "). scanf("%d", &entry[loop].age). fflush(stdin). /* flush the input stream in case of bad input */ /* input a salary as a float */ printf(" Salary : "). scanf("%f", &age, &salary). /* Print out the data that was input */ printf("\n\nTable %s\n",label). printf("Compiled by %s age %d $.2lf\n", name, age, salary). printf("-----\n"). for (loop=0;loop < 20;loop printf("M | %-20s | ] | .2lf\n", loop 1, entry[loop].name, entry[loop].age, entry[loop].salary).
```

```
printf("-----\n").
```

return 0. } 函数名: searchpath 功能: 搜索DOS路径 用法: char

\*searchpath(char \*filename). 程序例: #include #include int

```
main(void) { char *p. /* Looks for TLINK and returns a pointer
```

100Test 下载频道开通，各类考试题目直接下载。详细请访问

[www.100test.com](http://www.100test.com)