

C语言函数大全(h开头) PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/135/2021_2022_C_E8_AF_A_D_E8_A8_80_E5_87_BD_c97_135217.htm 函数名: harderr 功 能: 建立一个硬件错误处理程序 用 法: void harderr(int (*fptr)()). 程序例: /*This program will trap disk errors and prompt the user for action. Try running it with no disk in drive A: to invoke its functions.*/ #include #include #include #define IGNORE 0 #define RETRY 1 #define ABORT 2 int buf[500]. /*define the error messages for trapping disk problems*/ static char *err_msg[] = {"write protect", "unknown unit", "drive not ready", "unknown command", "data error (CRC)", "bad request", "seek error", "unknown media type", "sector not found", "printer out of paper", "write fault", "read fault", "general failure", "reserved", "reserved", "invalid disk change" }. error_win(char *msg) { int retval. cputs(msg). /*prompt for user to press a key to abort, retry, ignore*/ while(1) { retval= getch(). if (retval == 'a' || retval == 'A') { retval = ABORT. break. } if (retval == 'r' || retval == 'R') { retval = RETRY. break. } if (retval == 'i' || retval == 'I') { retval = IGNORE. break. } } return(retval). } /*pragma warn -par reduces warnings which occur due to the non use of the parameters errval, bp and si to the handler.*/ #pragma warn -par int handler(int errval,int ax,int bp,int si) { static char msg[80]. unsigned di. int drive. int errno. di=_DI. /*if this is not a disk error then it was another device having trouble*/ if (ax { /* report the error */ error_win("Device error"). /* and return to the program directly */

```
requesting abort */ hardretn(ABORT). } /* otherwise it was a disk  
error */ drive = ax amp. 0x00FF. /* report which error it was */  
sprintf(msg, "Error: %s on drive %c\r\nA)bort, R)etry, I)gnore: ",  
err_msg[errno], ' A ' drive). /* return to the program via dos  
interrupt 0x23 with abort, retry, or ignore as input by the user. */  
hardresume(error_win(msg)). return ABORT. } #pragma warn par  
int main(void) { /* install our handler on the hardware problem  
interrupt */ harderr(handler). clrscr(). printf("Make sure there is no  
disk in drive A:\n"). printf("Press any key ....\n"). getch().  
printf("Trying to access drive A:\n"). printf("fopen returned  
%p\n", fopen("A:temp.dat", "w")). return 0. } 100Test 下载频道开  
通，各类考试题目直接下载。详细请访问 www.100test.com
```