

C语言函数大全(d开头) PDF转换可能丢失图片或格式，建议
阅读原文

https://www.100test.com/kao_ti2020/135/2021_2022_C_E8_AF_AD_E8_A8_80_E5_87_BD_c97_135238.htm 函数名: delay 功能: 将程序的执行暂停一段时间(毫秒) 用法: void delay(unsigned milliseconds). 程序例: /* Emits a 440-Hz tone for 500 milliseconds */ #include int main(void) { sound(440). delay(500). nosound(). return 0. } 函数名: delline 功能: 在文本窗口中删去一行 用法: void delline(void). 程序例: #include int main(void) { clrscr(). cprintf("The function DELLINE 0deletes \ the line containing the\r\n"). cprintf("cursor and moves all lines \ below it one line up.\r\n"). cprintf("DELLINE operates within the \ currently active text\r\n"). cprintf("window. Press any key to \ continue . . ."). gotoxy(1,2). /* Move the cursor to the second line and first column */ getch(). delline(). getch(). return 0. } 函数名: detectgraph 功能: 通过检测硬件确定图形驱动程序和模式 用法: void far detectgraph(int far *graphdriver, int far *graphmode). 程序例: #include #include #include #include /* names of the various cards supported */ char *dname[] = { "requests detection", "a CGA", "an MCGA", "an EGA", "a 64K EGA", "a monochrome EGA", "an IBM 8514", "a Hercules monochrome", "an ATamp.gdriver, &.gmode). /* read result of detectgraph call */ errorcode = graphresult(). if (errorcode != grOk) /* an error occurred */ { printf("Graphics error: %s\n", \ grapherrormsg(errorcode)). printf("Press any key to halt:"). getch(). exit(1). /* terminate with an error code */ } /* display the information detected */ clrscr().

```
printf("You have %s video display \ card.\n", dname[gdriver]).  
printf("Press any key to halt:"). getch(). return 0. }
```

100Test 下载频道开通，各类考试题目直接下载。详细请访问
www.100test.com