

C语言函数大全(b开头) PDF转换可能丢失图片或格式 , 建议
阅读原文

https://www.100test.com/kao_ti2020/135/2021_2022_C_E8_AF_AD_E8_A8_80_E5_87_BD_c97_135248.htm 函数名: bar 功能: 画一个二维条形图 用法: void far bar(int left, int top, int right, int bottom). 程序例: #include #include #include #include int main(void) { /* request auto detection */ int gdriver = DETECT, gmode, errorcode. int midx, midy, i. /* initialize graphics and local variables */ initgraph(amp.gmode, ""). /* read result of initialization */ errorcode = graphresult(). if (errorcode != grOk) /* an error occurred */ { printf("Graphics error: %s\n", grapherrormsg(errorcode)). printf("Press any key to halt:"). getch(). exit(1). /* terminate with an error code */ } midx = getmaxx() / 2. midy = getmaxy() / 2. /* loop through the fill patterns */ for (i=SOLID_FILL. i { /* set the fill style */ setfillstyle(i, getmaxcolor()). /* draw the bar */ bar(midx-50, midy-50, midx 50, midy 50). getch(). } /* clean up */ closegraph(). return 0. } 函数名: bar3d 功能: 画一个三维条形图 用法: void far bar3d(int left, int top, int right, int bottom, int depth, int topflag). 程序例: #include #include #include #include int main(void) { /* request auto detection */ int gdriver = DETECT, gmode, errorcode. int midx, midy, i. /* initialize graphics, local variables */ initgraph(amp.gmode, ""). /* read result of initialization */ errorcode = graphresult(). if (errorcode != grOk) /* an error occurred */ { printf("Graphics error: %s\n", grapherrormsg(errorcode)). printf("Press any key to halt:"). getch(). exit(1). /* terminate with error code */ } midx = getmaxx() / 2. midy

```
= getmaxxy() / 2. /* loop through the fill patterns */ for
(i=EMPTY_FILL; i { /* set the fill style */ setfillstyle(i,
getmaxcolor()). /* draw the 3-d bar */ bar3d(midx-50, midy-50,
midx 50, midy 50, 10, 1). getch(). } /* clean up */ closegraph().
return 0. }
```

100Test 下载频道开通，各类考试题目直接下载。详细请访问 www.100test.com