

MySQL数据库函数详解(3) PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/137/2021_2022_MySQL_E6_95_B0_E6_8D_c98_137926.htm (5)

int mysql_data_seek(int result_id, int row_num). 由SELECT查询返回的每个结果集都有一个行游标，指示下一个提取行的函数(mysql_fetch_array()、mysql_fetch_object()或者mysql_fetch_row())调用将返回哪一行。mysql_data_seek()将给定结果集的指针设置到给定的行。行号的范围为0到mysql_num_rows()-1。如果行号合法，则mysql_data_seek()返回真，否则返回假。

```
$link=mysql_pconnect("localhost","sunsoft","suixiang") or die("Could not connect"). mysql_0select_db("samp_db") or die("Could not 0select database"). $query="SELECT last_name,first_name FROM president").
```

```
$result=mysql_query($query) or die("Query failed").
```

```
for($i=mysql_num_rows($result)-1;$i>=0;$i-) {
```

```
if(!mysql_data_seek($result,$i). { printf("Cannot seek to row %dn",$i). continue. } if(!$row=mysql_fetch_object($result))
```

```
continue. printf("%d %sn",$row->last_name,$row->first_name). }
```

```
mysql_free_result($result). ?> 100Test 下载频道开通，各类考试题目直接下载。详细请访问 www.100test.com
```