

Oracle9i到10g,空闲等待事件的变化 PDF转换可能丢失图片或格式 , 建议阅读原文

[https://www.100test.com/kao\\_ti2020/142/2021\\_2022\\_Oracle9i\\_E5\\_88\\_c102\\_142931.htm](https://www.100test.com/kao_ti2020/142/2021_2022_Oracle9i_E5_88_c102_142931.htm) 从Statspack的创建脚本中,我们可以看到从Oracle9i到Oracle10g,空闲等待事件的改变. 空闲等待事件在Statspack中,记录在系统表STATS\$IDLE\_EVENT中. 检查其创建脚本我们可以找到这些变化.这个脚本位于\$ORACLE\_HOME/rdbms/admin/spctab.sql 在Oracle9iR2中,空闲等待有:/\*

---

```
-- */create table STATS$IDLE_EVENT(event varchar2(64) not null,constraint STATS$IDLE_EVENT_PK primary key (event) using index tablespace amp.tablespace_name storage (initial 100k next 100k pctincrease 0)) tablespace amp.tablespace_name storage (initial 100k next 100k pctincrease 0) pctfree 5 pctused 40.insert into STATS$IDLE_EVENT (event) values (smon timer).insert into STATS$IDLE_EVENT (event) values (pmon timer).insert into STATS$IDLE_EVENT (event) values (rdbms ipc message).insert into STATS$IDLE_EVENT (event) values (Null event).insert into STATS$IDLE_EVENT (event) values (parallel query dequeue).insert into STATS$IDLE_EVENT (event) values (pipe get).insert into STATS$IDLE_EVENT (event) values (client message).insert into STATS$IDLE_EVENT (event) values (SQL*Net message to client).insert into STATS$IDLE_EVENT (event) values (SQL*Net message from client).insert into STATS$IDLE_EVENT (event) values (SQL*Net more data from
```

```
client).insert into STATS$IDLE_EVENT (event) values (dispatcher
timer).insert into STATS$IDLE_EVENT (event) values (virtual
circuit status).insert into STATS$IDLE_EVENT (event) values (lock
manager wait for remote message).insert into
STATS$IDLE_EVENT (event) values (PX Idle Wait).insert into
STATS$IDLE_EVENT (event) values (PX Deq: Execution
Msg).insert into STATS$IDLE_EVENT (event) values (PX Deq:
Table Q Normal).insert into STATS$IDLE_EVENT (event) values
(wakeup time manager).insert into STATS$IDLE_EVENT (event)
values (slave wait).insert into STATS$IDLE_EVENT (event) values
(i/o slave wait).insert into STATS$IDLE_EVENT (event) values
(jobq slave wait).insert into STATS$IDLE_EVENT (event) values
(null event).insert into STATS$IDLE_EVENT (event) values (gcs
remote message).insert into STATS$IDLE_EVENT (event) values
(gcs for action).insert into STATS$IDLE_EVENT (event) values
(ges remote message).insert into STATS$IDLE_EVENT (event)
values (queue messages).commit.create public synonym
STATS$IDLE_EVENT for STATS$IDLE_EVENT./*
```

---

```
-- */ 在Oracle10gR2中,这个数字大大增加:/*
```

---

```
-- */create table STATS$IDLE_EVENT(event varchar2(64) not
null,constraint STATS$IDLE_EVENT_PK primary key (event)
using index tablespace amp.tablespace_name storage (initial 100k
next 100k pctincrease 0)) tablespace amp.tablespace_name storage
(initial 100k next 100k pctincrease 0) pctfree 5 pctused 40.insert into
```

STAT\$IDLE\_EVENT (event) values (smon timer).insert into  
STAT\$IDLE\_EVENT (event) values (pmon timer).insert into  
STAT\$IDLE\_EVENT (event) values (rdbms ipc message).insert  
into STAT\$IDLE\_EVENT (event) values (Null event).insert into  
STAT\$IDLE\_EVENT (event) values (parallel query  
dequeue).insert into STAT\$IDLE\_EVENT (event) values (pipe  
get).insert into STAT\$IDLE\_EVENT (event) values (client  
message).insert into STAT\$IDLE\_EVENT (event) values  
(SQL\*Net message to client).insert into STAT\$IDLE\_EVENT  
(event) values (SQL\*Net message from client).insert into  
STAT\$IDLE\_EVENT (event) values (SQL\*Net more data from  
client).insert into STAT\$IDLE\_EVENT (event) values (dispatcher  
timer).insert into STAT\$IDLE\_EVENT (event) values (virtual  
circuit status). 100Test 下载频道开通，各类考试题目直接下载  
。 详细请访问 [www.100test.com](http://www.100test.com)