

Oracle9i到10g,空闲等待事件的变化(1) PDF转换可能丢失图片或格式，建议阅读原文

[https://www.100test.com/kao\\_ti2020/143/2021\\_2022\\_Oracle9i\\_E5\\_88\\_c102\\_143249.htm](https://www.100test.com/kao_ti2020/143/2021_2022_Oracle9i_E5_88_c102_143249.htm) 从statspack的创建脚本中,我们可以看到从oracle9i到oracle10g,空闲等待事件的改变.空闲等待事件在statspack中,记录在系统表stats\$idle\_event中.检查其创建脚本我们可以找到这些变化.这个脚本位于\$oracle\_home/rdbms/admin/spctab.sql 在oracle9ir2中,空闲等待有:/\*

---

```
-- */create table stats$idle_event(event varchar2(64) not
null,constraint stats$idle_event_pk primary key (event) using index
tablespace amp.tablespace_name storage (initial 100k next 100k
pctincrease 0)) tablespace amp.tablespace_name storage (initial 100k
next 100k pctincrease 0) pctfree 5 pctused 40.insert into
stats$idle_event (event) values (smon timer).insert into
stats$idle_event (event) values (pmon timer).insert into
stats$idle_event (event) values (rdbms ipc message).insert into
stats$idle_event (event) values (null event).insert into
stats$idle_event (event) values (parallel query dequeue).insert into
stats$idle_event (event) values (pipe get).insert into stats$idle_event (event)
values (client message).insert into stats$idle_event (event)
values (sql*net message to client).insert into stats$idle_event (event)
values (sql*net message from client).insert into stats$idle_event (event)
values (sql*net more data from client).insert into
stats$idle_event (event) values (dispatcher timer).insert into
```

stats\$idle\_event (event) values (virtual circuit status).insert into  
stats\$idle\_event (event) values (lock manager wait for remote  
message).insert into stats\$idle\_event (event) values (px idle  
wait).insert into stats\$idle\_event (event) values (px deq: execution  
msg).insert into stats\$idle\_event (event) values (px deq: table q  
normal).insert into stats\$idle\_event (event) values (wakeup time  
manager).insert into stats\$idle\_event (event) values (slave  
wait).insert into stats\$idle\_event (event) values (i/o slave wait).insert  
into stats\$idle\_event (event) values (jobq slave wait).insert into  
stats\$idle\_event (event) values (null event).insert into  
stats\$idle\_event (event) values (gcs remote message).insert into  
stats\$idle\_event (event) values (gcs for action).insert into  
stats\$idle\_event (event) values (ges remote message).insert into  
stats\$idle\_event (event) values (queue messages).commit.create  
public synonym stats\$idle\_event for stats\$idle\_event. 100Test 下载  
频道开通，各类考试题目直接下载。详细请访问  
[www.100test.com](http://www.100test.com)