

RHCE302重要学习知识点 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/144/2021_2022_RHCE302_E9_87_8D_c103_144085.htm

INSTALLATION Use the right boot disk for the installation: boot.img - Standard installation bootnet.img - Network installation pcmcia.img - PCMCIA required installation

Install LILO in an appropriate location: MBR - If LILO will be the default bootloader First partition of boot sector - If you're using another OS bootloader

LINUX FILESYSTEM The root filesystem is made up of 12 directories by default: /bin /home /proc /dev /opt /usr /etc /lost found /var /sbin /mnt /usr/local

KERNEL COMPILING

Three options are available for configuring a kernel: make config make menuconfig make xconfig

There are two types of kernel images: zImage (small kernel images) bzImage (compressed kernel images)

The seven steps for compiling a kernel are: make configuration (makeconfig, make menuconfig, or make xconfig) make dep make clean make bzImage (or zImage) make modules make modules_install configure LILO and reboot

Three shorter steps for compiling a kernel are: make configuration (make config, make menuconfig, or make xconfig) make dep clean bzImage

modules modules_install configure LILO and reboot

X WINDOW SYSTEM Three X configuration tools are: Xconfigurator XF86Setup xf86config

APACHE The main configuration directory is /etc/httpd/conf/. The main Apache configuration file is httpd.conf, used for httpd server configuration. To configure a virtual host, follow these steps: Set NameVirtualHost (NameVirtualHost

192.168.0.1). Set VirtualHost (). Set DocumentRoot. Set ServerName. Set ErrorLog. Set TransferLog. Close VirtualHost (). Restart httpd (/etc/rc.d/init.d/httpd restart). EMAIL There are three components of email: MTA - Mail transfer agent (sendmail) MDA - Mail delivery agent (procmail) MUA - Mail user agent (Pine, Elm, Mutt, Netscape) 100Test 下载频道开通，各类考试题目直接下载。 详细请访问 www.100test.com