ar2831ar1820 br304ipsecvpn   PDF

: ar2831   :
ar1820 br304   :   192.168.0.0/24
    192.168.1.0- 192.168.6.0/24   [Ar2831]dis
cur#sysname Ar2831#FTP server enable#l2tp domain
suffix-separator @#ike local-name center#radius scheme
system#domain system#local-user huaweipassword cipher
(3F7#N"9*%G.Q=^Q`MAF4service-type telnetlevel 3#ike proposal
1 authentication-algorithm md5#ike peer fen1exchange-mode
aggressivepre-shared-key lzljid-type nameremote-name
fen1remote-address 222.x.200.x(   )nat
traversal#ike peer fen2exchange-mode aggressivepre-shared-key
abcdid-type nameremote-name fen2nat traversal#ike peer
fen3exchange-mode aggressivepre-shared-keyabcdid-type
nameremote-name fen3 nat traversal#ike peer fen4exchange-mode
aggressivepre-shared-key abcdid-type nameremote-name fen4nat
traversal#ike peer fen5exchange-mode aggressivepre-shared-key
abcdid-type nameremote-name fen5nat traversal#ipsec proposal
1234#ipsec policy-template temp_fen 1ike-peer fen1proposal
1234#ipsec policy-template temp_fen 2 ike-peer fen2proposal
1234#ipsec policy-template temp_fen 3ike-peer fen3proposal
1234#ipsec policy-template temp_fen 4ike-peer fen4proposal
1234#ipsec policy-template temp_fen 5ike-peer fen5proposal
1234#ipsec policy all_peer 1 isakmp template temp_fen#interface

Aux0async mode flow#interface Ethernet0/0ip address 218.x.135.x 255.255.255.248nat outbound 3001ipsec policy all_peer#interface Ethernet0/1ip address 192.168.0.1 255.255.255.0#interface NULL0#acl number 3001rule 0 deny ip source 192.168.0.0 0.0.0.255 destination 192.168.0.0.0.255.255rule 1 permit ip source 192.168.0.0 0.0..255rule 2 deny ip#ip route-static 0.0.0.0 0.0.0.0 218.x.135.1 preference 60#user-interface con 0user-interface aux 0user-interface vty 0 4authentication-mode schemeuser privilege level 3#return [Ar2831] [fen3]dis cur#sysname fen3#local-user test password simple testlocal-user test service-type ppplocal-user user password simple 1234#aaa enable#ike peer fen3exchange-mode aggressivepre-shared-key abcdefgid-type nameremote-name centerremote-address 218.x.135.x#ipsec proposal huawei#ipsec policy mypolicy 1 isakmpsecurity acl 3000ike-peer fen3proposal huawei#interface Ethernet1/0tcp mss 1024ip address 192.168.3.1 255.255.255.0# interface Ethernet2/0speed 10 duplex full tcp mss 1024 ip address 218.x.215.x 255.255.255.0nat outbound 3001ipsec policy mypolicy#interface NULL0#acl number 3000rule 0 permit ip source 192.168.0.0 0.0.0.255 destination 192.168.0.0 0.0.0.255acl number 3001rule 1 deny ip source 192.168.0.0 0.0.0.255 destination 192.168.0.0 0.0.0.255rule 2 permit ip source 192.168.3.0 0.0.0.255#ip route-static 0.0.0.0 0.0.0.0 218.x.215.1 preference 60#user-interface con 0user-interface vty 0 4user privilege level 3set authentication password simple test#return 100Test

www.100test.com