

OracleXMLDB占用了8080端口 PDF转换可能丢失图片或格式
， 建议阅读原文

https://www.100test.com/kao_ti2020/227/2021_2022_OracleXMLD_c102_227680.htm 解决办法：修改XMLDB的端口设置 禁止XMLDB监听端口

Change XMLDB Ports This document explains how to change the default ports (8080 for HTTP and 2100 for FTP) in XMLDB. Oracle XMLDB uses the ports 2100/8080 by default. Sometimes there are problem with other web servers (e.g. JBOSS) running on the same port. Even if the package dbms_xdb is granted to PUBLIC you need DBA privileges to change the ports. 用

系统管理员身份登陆-- change HTTP port from 8080 to 8083 call

```
dbms_xdb.cfg_0update(0updateXML(dbms_xdb.cfg_get(),  
/xdbconfig/sysconfig/protocolconfig/httpconfig/http-port/text(),
```

```
8083)).-- change FTP port from 2100 to 2111 call
```

```
dbms_xdb.cfg_0update(0updateXML( dbms_xdb.cfg_get(),  
/xdbconfig/sysconfig/protocolconfig/ftpconfig/ftp-port/text() ,
```

```
2111)).-- refresh settings exec dbms_xdb.cfg_refresh. 命令示例
```

```
: SQL> call
```

```
dbms_xdb.cfg_0update(0updateXML(dbms_xdb.cfg_get(), 2  
/xdbconfig/sysconfig/protocolconfig/httpconfig/http-port/text(),80  
81)) 3 /SQL> commit. Commit complete. SQL> exec
```

```
dbms_xdb.cfg_refresh.[oracle@test11 oracle]$ sqlplus /nolog
```

```
SQL*Plus: Release 9.2.0.4.0 - Production on Sat Aug 6 14:24:49 2005  
Copyright (c) 1982, 2002, Oracle Corporation. All rights reserved.
```

```
SQL> connect / as sysdba.Connected.-- 把HTTP/WEBDAV端口
```

```
从8080改到8081SQL> call
```

dbms_xdb.cfg_0update(0updateXML(dbms_xdb.cfg_get(), 2
/xdbconfig/sysconfig/protocolconfig/httpconfig/http-port/text(),80
81)) 3 / 100Test 下载频道开通，各类考试题目直接下载。详细
请访问 www.100test.com