

squid13 solaris10反向代理配置全攻略 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/240/2021_2022_squid13_so_c103_240652.htm 1，准备工作：Solaris10，squid-2.6.STABLE13 2

，开始安装和配置：1) 查看和修改最大连接数：#ulimit -a
core file size (blocks, -c) unlimited data seg size (kbytes, -d)
unlimited file size (blocks, -f) unlimited open files (-n) 65536 pipe
size (512 bytes, -p) 10 stack size (kbytes, -s) 8480 cpu time (seconds,
-t) unlimited max user processes (-u) 8485 virtual memory (kbytes,
-v) unlimited 修改：vi /usr/include/sys/types.h #define

```
FD_SETSIZE 10240 #ifndef _SYS_TYPES_H #define
```

```
_SYS_TYPES_H 2) 将squid软件解压和安装到制定目录：
```

```
./configure --prefix=/usr/local/squid --disable-internal-dns
```

```
--enable-useragent-log --enable-referer-log ( 可以看到连接数已经修改为10240 ) make ; make install ; 3) 在squid.conf文件里
```

```
修改配置：vi /usr/local/squid/etc/squid.conf 增加和修改的部分
```

```
： http_port 80 accel vhost hierarchy_stoplist cgi-bin ? acl QUERY
```

```
urlpath_regex cgi-bin \? cache deny QUERY acl apache rep_header
```

```
Server ^Apache broken_vary_encoding allow apache cache_mem
```

```
1024 MB cache_dir ufs /export/home/squid/cache 4000 16 256
```

```
access_log /export/home/squid/logs/access.log squid cache_log
```

```
/export/home/squid/logs/cache.log cache_store_log
```

```
/export/home/squid/logs/store.log pid_filename
```

```
/export/home/squid/logs/squid.pid cache_dns_program
```

```
/usr/local/squid/libexec/dnsserver dns_children 10 hosts_file
```

```
/etc/hosts refresh_pattern ^ftp: 1440 20% 10080 refresh_pattern
```

```
^gopher: 1440 0% 1440 refresh_pattern .jsp 0 20% 0 refresh_pattern .
0 20% 2 acl acceleratedHostSCUT dstdomain .abc.com acl
acceleratedProtocol protocol HTTP acl acceleratedPort port 80 acl
all src 0.0.0.0/0.0.0.0 acl manager proto cache_object acl localhost src
127.0.0.1/255.255.255.255 acl to_localhost dst 127.0.0.0/8 acl
SSL_ports port 443 acl Safe_ports port 80 # http acl Safe_ports port
21 # ftp acl Safe_ports port 443 # https acl Safe_ports port 70 #
gopher acl Safe_ports port 210 # wais acl Safe_ports port 1025-65535
# unregistered ports acl Safe_ports port 280 # http-mgmt acl
Safe_ports port 488 # gss-http acl Safe_ports port 591 # filemaker acl
Safe_ports port 777 # multiling http acl CONNECT method
CONNECT http_access allow acceleratedProtocol acceleratedPort
acceleratedHostABC http_access allow manager localhost
http_access deny manager http_access deny !Safe_ports http_access
deny CONNECT !SSL_ports http_access deny all http_reply_access
allow all icp_access allow all visible_hostname webcache3.abc.com
logfile_rotate 10 always_direct allow acceleratedHostABC
coredump_dir /export/home/squid/cache 100Test 下载频道开通
, 各类考试题目直接下载。详细请访问 www.100test.com
```