

DebianLinux操作系统下启动Telnet服务[2] PDF转换可能丢失图片或格式，建议阅读原文

[https://www.100test.com/kao\\_ti2020/244/2021\\_2022\\_DebianLinu\\_c103\\_244542.htm](https://www.100test.com/kao_ti2020/244/2021_2022_DebianLinu_c103_244542.htm) 我们现在来连接一下 root@2[/]# telnet 192.168.1.254 Trying 192.168.1.254... Connected to 192.168.1.254. Escape character is ^]. lcnja.8800.org login: root Login incorrect lcnja.8800.org login: lcnja Password: Last login: Mon Sep 27 20:51:33 2004 from localhost.localdomain on pts/3 Linux debian 2.6.8-1-686 #1 Tue Sep 14 00:22:58 EDT 2004 i686 GNU/Linux The programs included with the Debian GNU/Linux system are free software. the exact distribution terms for each program are described in the individual files in /usr/share/doc/\*/copyright. Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent permitted by applicable law. lcnja@lcnja:~\$ 从上面我们可以看到我们已经连接成功了，但是使用root连接的时候会失败，因为默认的安全设置是限制root用户使用telnet连接主机的 本来因为telnet是明文传输的，所以处于安全考虑才限制了root从telnet登陆，如果你需要使用，那么如下修改 root@2[/]# nano /etc/pam.d/login ## The PAM configuration file for the Shadow `login service ## NOTE: If you use a session module (such as kerberos or NIS ) # that retains persistent credentials (like key caches, etc), you # need to enable the `CLOSE\_SESSIONS option in /etc/login.defs # in order for login to stay around until after logout to call # pam\_close\_session() and cleanup. ## Outputs an issue file prior to each login prompt (Replaces the # ISSUE\_FILE option from login.defs). Uncomment for use # auth required pam\_issue.so

```
issue=/etc/issue # Disallows root logins except on ttys listed in
/etc/securetty # (Replaces the `CONSOLE` setting from login.defs) #
把下面在行注释掉 # auth requisite pam_securetty.so # Disallows
other than root logins when /etc/nologin exists # (Replaces the
`NOLOGINS_FILE` option from login.defs) auth requisite
pam_nologin.so # This module parses /etc/environment (the
standard for setting # environ vars) and also allows you to use an
extended config # file /etc/security/pam_env.conf. # (Replaces the
`ENVIRON_FILE` setting from login.defs) auth required
pam_env.so # Standard Un*x authentication. The "nullok" line
allows passwordless # accounts. @include common-auth # This
allows certain extra groups to be granted to a user # based on things
like time of day, tty, service, and user. # Please uncomment and edit
/etc/security/group.conf if you # wish to use this. # (Replaces the
`CONSOLE_GROUPS` option in login.defs) # auth optional
pam_group.so # Uncomment and edit /etc/security/time.conf if you
n 好，现在一个telnet我们就在debian下面架设好了，当然最后
一步本人不建议你做 因为telnet是内镶在xinetd这个服务里面的
的，所以如果你要启动或者是要停止该服务就要 root@2[/]#
/etc/init.d/xinetd force-reload reload restart start stop 看上面的自
己选择 100Test 下载频道开通，各类考试题目直接下载。详细
请访问 www.100test.com
```