

详细讲解：Qmail软件加装自动杀毒的方法 PDF转换可能丢失
图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/252/2021_2022__E8_AF_A6_E7_BB_86_E8_AE_B2_E8_c103_252930.htm Qmail-scan McAfee
VirusScan Command Line qmail-scan的网站

<http://qmail-scanner.sourceforge.net/>，最新版本1.22 需要依赖的
程序 reformime (来自 Mail0drop 1.3.8) Perl 5.6.1 Perl module
Time::HiRes Perl module DB_File (可能不需要或者系统已经存在)
Perl module Sys::Syslog (可能不需要或者系统已经存在)

TNEF unpacker 这里介绍手动安装，主要是不想重新编

译Qmail加入QMAILQUEUE 安装McAfee VirusScan Command
Line,并且将uvscan In到/usr/local/bin 和 .so文件In到/usr/local/lib
tar zxf qmail-scanner-1.22.gz cd qmail-scanner-1.22 配

置qmail-scanner,路径自定义,yourdomain替换为你的域名,详细
的参看./configure --help./configure --spooldir /mail/qmailscan

--qmaildir/mail/qmail --bindir /mail/qmail/bin

--qmail-queue-binary/mail/qmail/bin/qmail-queue.real --admin
root--domain yourdomain --notify recip --local-domains

yourdomain--silent-viruses auto --lang en_GB --debug no --unzip1

--add-dscr-hdrs 0 --archive 0 --redundant no --log-details0

--log-crypto 0 --fix-mime 2 --scanners "uvscan"--ignore-eol-check

0 --no-QQ-check 添加用户和组pw groupadd qscand -g 65530pw

useradd qscand -g qscand -d /mail/qmailscan -s /nonexistent -u

65530 创建目录mkdir -p /mail/qmailscanmkdir -p

/mail/qmailscan/quarantine/tmp

/mail/qmailscan/quarantine/cur/mail/qmailscan/quarantine/newmk

```
dir -p /mail/qmailscan/working/tmp /mail/qmailscan/working/cur
/mail/qmailscan/working/newmkdir -p
/mail/qmailscan/archive/tmp /mail/qmailscan/archive/cur
/mail/qmailscan/archive/new 复制文件，设置权限cp
quarantine-attachments.txt /mail/qmailscan/chown -R
qscand.qscand /mail/qmailscan/cp qmail-scanner-queue.pl
/mail/qmail/bin/qmail-scanner-queue.plchown qscand.qscand
/mail/qmail/bin/qmail-scanner-queue.plchmod 4755
/mail/qmail/bin/qmail-scanner-queue.pl 初始化qmail-scan,代
替qmail-queue先调用/mail/qmail/bin/qmail-scanner-queue.pl
-h/mail/qmail/bin/qmail-scanner-queue.pl
-z/mail/qmail/bin/qmail-scanner-queue.pl -gmv
/mail/qmail/bin/qmail-queue /mail/qmail/bin/qmail-queue.realln -s
/mail/qmail/bin/qmail-scanner-queue.pl
/mail/qmail/bin/qmail-queue mcafee病毒库自动更新脚
本0update.sh, 放在uvscan目录下
面#!/bin/shinstall_Directory=`dirname $0`mkdir
/tmp/dat-0updatescd
/tmp/dat-0updatescurrent_version=`$install_directory/uvscan
--version | grep "Virus data file" | awk { print substr($4,2,4) }`ftp
"ftp://ftp.nai.com/pub/datfiles/english/dat-*.tar"new_version=`echo
dat-*.tar | awk { print substr($1,5,4) }`if [ "$current_version" -ge
"$new_version" ] then echo "No new .DATs available at this time"
echo "Currently installed version: $current_version" echo "Version
on FTP site: $new_version" else tar -xf dat-*.tar for file in `tar -tf
dat-*.tar` do newfile=`echo $file | tr [A-Z] [a-z]` mv -f ./file
```

```
"$install_directory/$newfile" done
current_version=`$install_directory/uvscan --version | grep "Virus
data file" | awk { print substr($4,2,4) }` if [ ! "$current_version" -eq
"$new_version" ] then echo "DAT file 0updates did not work
correctly." echo "Please try manually." else echo "DAT file 0updates
successful" echo "Currently installed version: $current_version" fificd
/rm -rf /tmp/dat-0updateschmod x 0update.sh 做个crond每6小时
更新一次 100Test 下载频道开通，各类考试题目直接下载。详
细请访问 www.100test.com
```