

运用类反射机制简化Struts应用程序开发 PDF转换可能丢失图片或格式，建议阅读原文

[https://www.100test.com/kao\\_ti2020/268/2021\\_2022\\_\\_E8\\_BF\\_90\\_](https://www.100test.com/kao_ti2020/268/2021_2022__E8_BF_90_)

E7\_94\_A8\_E7\_B1\_BB\_E5\_c67\_268983.htm 1、 先定义Action FormBean: package com.bhsky.webis.system.import org.apache.struts.action.\*.import javax.servlet.http.\*. public class UsersActionForm extends ActionForm {private String usr\_id.private String usr\_name.public void setUsr\_id(String usr\_id) { this.usr\_id = usr\_id.}public String getUsr\_id() { return usr\_id.}public String getUsr\_memo() { return usr\_memo.}public void setUsr\_name(String usr\_name) { this.usr\_name = usr\_name.}}2、 编写通用的为ActionFormBean赋值的方法： //Function: 完成ResultSet对象向ArrayList对象为集合的对象的转化 //Para:sql, 指定的查询Sql //Para:className,Sql相对应得JavaBean/FormBean类的名字 //Return:以类className为一条记录的结果集， //完成ResultSet对象向ArrayList对象为集合的className对象的转化 public ArrayList Select(String sql,String className){ ArrayList paraList=new ArrayList(). try{ if (conn == null){ Connection(). } PreparedStatement stmt = conn.prepareStatement(sql). ResultSet rs = stmt.executeQuery(). String recordValue="". Object c1=null. paraList=new ArrayList(). ResultSetMetaData rsmd = rs.getMetaData(). int columnCount = rsmd.getColumnCount(). while (rs.next()){ c1=Class.forName(className).newInstance(). for (int i=1. i3、 在JavaBean封装的商业逻辑中调用Select方法，然后在JSP页面上显示出来： //Function:取得用户列表 //Para: //Return:返回用户列表 public ArrayList getUsers(){ ArrayList

```
ret=null. DatabaseManage db=new DatabaseManage(). String sql="
0select usr_id,usr_name " " from users " . ret=db.Select(sql,"
com.bhsky. webis.system.UsersActionForm"). return ret. }4、
在Action的execute方法中调用getUsers()方法： public
ActionForward execute(ActionMapping actionMapping,
ActionForm actionForm, HttpServletRequest request,
HttpServletResponse httpServletResponse) { /** @todo: complete
the business logic here, this is just a skeleton.*/ UsersActionForm
uaf=(UsersActionForm)actionForm. SystemService ubb=new
SystemService(). ArrayList userList=ubb.getUsers().
request.setAttribute("userList",userList). ActionForward
actionForward=actionMapping.findForward(url). return
actionForward. }5、 在JSP中显示： 用户ID 姓&#160;名
100Test 下载频道开通，各类考试题目直接下载。详细请访问
www.100test.com
```