

Catalyst6509防火墙模块配置 PDF转换可能丢失图片或格式，  
建议阅读原文

[https://www.100test.com/kao\\_ti2020/271/2021\\_2022\\_Catalyst65\\_c101\\_271545.htm](https://www.100test.com/kao_ti2020/271/2021_2022_Catalyst65_c101_271545.htm) 分成两个部分进行配置：Catalyst 6509加模块，  
可以看成是两个设备的连接，即一个防火墙加一个路由器。

```
FWSM : nameif vlan3 outside security0nameif vlan5 inside
security100ip address outside 192.168.200.2 255.255.255.0ip address
inside 192.168.220.1 255.255.255.0route outside 0 0 192.168.200.1
1nat (inside) 1 10.1.2.0 255.255.255.0global (outside) 1
interfaceaccess-list out extended permit ip any anyaccess-group out
in interface insideicmp permit any insideicmp permit any outside
switch : firewall module 8 vlan-group 1 //不配置该语句，防火墙
上面的vlan接口不会upfirewall vlan-group 1 3-8interface vlan 3 //
该配置决定防火墙所在的位置ip address 192.168.200.1
255.255.255.0no shut 100Test 下载频道开通，各类考试题目直
接下载。详细请访问 www.100test.com
```