

如何获取M QLServer,Oracel,Acce 中的数据字典信息 PDF转换
可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/284/2021_2022_E5_A6_82_E4_BD_95_E8_8E_B7_E5_c97_284918.htm

----- MS
SQLServer -----

----- 表说明 SELECT
dbo.sysobjects.name AS TableName, dbo.sysproperties.[value] AS
TableDesc FROM dbo.sysproperties INNER JOIN dbo.sysobjects
ON dbo.sysproperties.id = dbo.sysobjects.id WHERE
(dbo.sysproperties.smallid = 0) ORDER BY dbo.sysobjects.name --
字段说明 SELECT dbo.sysobjects.name AS TableName,
dbo.syscolumns.colid, dbo.syscolumns.name AS ColName,
dbo.sysproperties.[value] AS ColDesc FROM dbo.sysproperties
INNER JOIN dbo.sysobjects ON dbo.sysproperties.id =
dbo.sysobjects.id INNER JOIN dbo.syscolumns ON
dbo.sysobjects.id = dbo.syscolumns.id AND
dbo.sysproperties.smallid = dbo.syscolumns.colid ORDER BY
dbo.sysobjects.name, dbo.syscolumns.colid --主键、外键信息(简
化)
0select c_obj.name as CONSTRAINT_NAME ,t_obj.name as
TABLE_NAME ,col.name as COLUMN_NAME ,case col.colid
when ref.fkey1 then 1 when ref.fkey2 then 2 when ref.fkey3 then 3
when ref.fkey4 then 4 when ref.fkey5 then 5 when ref.fkey6 then 6
when ref.fkey7 then 7 when ref.fkey8 then 8 when ref.fkey9 then 9
when ref.fkey10 then 10 when ref.fkey11 then 11 when ref.fkey12
then 12 when ref.fkey13 then 13 when ref.fkey14 then 14 when

ref.fkey15 then 15 when ref.fkey16 then 16 end as
ORDINAL_POSITION from sysobjects c_obj ,sysobjects t_obj
,syscolumns col ,sysreferences ref where permissions(t_obj.id) != 0
and c_obj.xtype in (@#F @#) and t_obj.id = c_obj.parent_obj and
t_obj.id = col.id and col.colid in
(ref.fkey1,ref.fkey2,ref.fkey3,ref.fkey4,ref.fkey5,ref.fkey6,
ref.fkey7,ref.fkey8,ref.fkey9,ref.fkey10,ref.fkey11,ref.fkey12,
ref.fkey13,ref.fkey14,ref.fkey15,ref.fkey16) and c_obj.id = ref.constid
union 0select i.name as CONSTRAINT_NAME ,t_obj.name as
TABLE_NAME ,col.name as COLUMN_NAME ,v.number as
ORDINAL_POSITION from sysobjects c_obj ,sysobjects t_obj
,syscolumns col ,master.dbo.spt_values v ,sysindexes i where
permissions(t_obj.id) != 0 and c_obj.xtype in (@#UQ@# ,@#PK@#)
and t_obj.id = c_obj.parent_obj and t_obj.xtype = @#U@# and
t_obj.id = col.id and col.name =
index_col(t_obj.name,i.indid,v.number) and t_obj.id = i.id and
c_obj.name = i.name and v.number > 0 and v.number and v.type =
@#P@# order by CONSTRAINT_NAME, ORDINAL_POSITION
--主键、外键对照(简化) 0select fc_obj.name as
CONSTRAINT_NAME ,i.name as
UNIQUE_CONSTRAINT_NAME from sysobjects fc_obj
,sysreferences r ,sysindexes i ,sysobjects pc_obj where
permissions(fc_obj.parent_obj) != 0 and fc_obj.xtype = @#F@# and
r.constid = fc_obj.id and r.rkeyid = i.id and r.rkeyindid = i.indid and
r.rkeyid = pc_obj.id 100Test 下载频道开通，各类考试题目直接
下载。详细请访问 www.100test.com