



security advantages because it prevents the so-called IP spoofing , # however it can pose problems if you use asymmetric routing ( packets from you # to a host take a different path than packets from that host to you ) or if # you operate a non-routing host which has several IP addresses on different # interfaces. To turn rp\_filter off , uncomment the lines below : # if [ -r /proc/sys/net/ipv4/conf/all/rp\_filter ] ; then # echo "Disabling rp\_filter....." # echo 0 > /proc/sys/net/ipv4/conf/all/rp\_filter # fi 可见 , slackware7的系统没有显式打开rp\_filter , 因此我们建议的解决方法是 : 在说明后面加入 echo "Enableing rp\_filter....." echo 1 > /proc/sys/net/ipv4/conf/all/rp\_filter 这样就可以打开rp\_filter设置。 3、TCP\_SYNCOOKIES ( 在2.2.x内核下关闭 ) 用于防止TCP\_SYN攻击的syn-cookies在2.0.x内核下是打开的 ( 缺省 ) , 但在2.2.x内核下却被关闭 ( 缺省 ) 了。管理员应该将其恢复为打开状态 , 这样能保护系统免受SYN flood攻击。 100Test 下载频道开通 , 各类考试题目直接下载。详细请访问 [www.100test.com](http://www.100test.com)