

SQL中与IP相关的常见问题 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/460/2021_2022_SQL_E4_B8_AD_E4_B8_8EI_c98_460915.htm 1:得到客户端的ip地

```
址/***** ip *****/declare @ip varchar(20),@hst
varchar(20),@sql varchar(100)declare @str varchar(100)set
@str=ping host_name()create table #tmp(aa varchar(200))insert
#tmp exec master..xp_cmdshell @str0select top 1 @ip =
replace(left(aa,charindex(:,aa)-1),reply from ,) from #tmp where aa
like reply from %:%0drop table #tmp0select @ip2:得到网卡的物理
地址create table #tb(re varchar(255))insert into #tb exec
master..xp_cmdshell ipconfig /all0select 网卡物理地
址=substring(re,charindex(:,re) 1,255) from #tb where re like
%physical address. . . . .:%0drop table #tb3: 将ip地址段转成每
三位用点号分开 create function getip(@a varchar(15))returns
varchar(15)asbegindeclare @s varchar(15)set @s = while
charindex(.,@a) > 0begin set @s = @s right(000
left(@a,charindex(.,@a)),4) set @a =
right(@a,len(@a)-charindex(.,@a))endset @s = @s right(000
@a,3)return @send/*0select dbo.getip(202.1.110.2)-----
202.001.110.002 ( 所影响的行数为 1 行 ) */--0drop function getip
```

100Test 下载频道开通，各类考试题目直接下载。详细请访问

www.100test.com