

表的许多分区被意外0drop用rman不完全恢复 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/462/2021_2022__E8_A1_A8_E7_9A_84_E8_AE_B8_E5_c102_462010.htm

如果表的很多分区被意外0drop，需要利用带库上的备份集在测试机上做不完全恢复，具体日期需要达到一个特定的时间，那么我们可以参考下文。首先需要用logminer查出删除语句：uncompress

```
/oracle/oradata/xxx/xxx.ARC.Z
```

```
...beginsys.dbms_logmnr.add_logfile(/oracle/oradata/xxx/xxx.ARC )....end.begin sys.dbms_logmnr.start_logmnr(Options =>
```

```
sys.dbms_logmnr.DICT_FROM_ONLINE_CATALOG).
```

```
end.create table xsb_logminer_1 as 0select timestamp,
```

```
seg_name,operation, sql_redo from V$LOGMNR_CONTENTS
```

```
where seg_owner=XXX and operation=DDL and sql_redo like
```

```
ALTER TABLE XXX DROP PARTITION %.BEGIN
```

```
sys.dbms_logmnr.end_logmnr().END. 然后在生产库上创
```

建pfile：create pfile=... from spfile. 需要从带库上恢复rman备份集至生产机上，将此备份集FTP至测试机上，连同pfile文件。

在测试机上创建与生产机上相同目录，admin 在测试机

上创建新实例orapwd file=... password=xxx 然后修改pfile文件内容，改变control_files内容 启动新实例export

```
ORACLE_SID=xxxsqlplus / as sysdba startup nomount
```

```
pfile=/home/oracle/init_XXX.ora.create spfile from
```

```
pfile=/home/oracle/init_XXX.ora.exitRMAN target sys/xxxrestore
```

```
controlfile from ....startup mount--crosscheck backup.list
```

```
backup.run {set newname for datafile 1 to
```

/oracle/oradata/xxx/system01.dbf.set newname for datafile 2 to
/oracle/oradata/xxx/undo01.dbf.set newname for datafile 3 to
/oracle/oradata/xxx/sysaux01.dbf.set newname for datafile 6 to
/oracle/oradata/xxx/pay_ts01.dbf.restore datafile 1.restore datafile
2.restore datafile 3. restore datafile 6.}(注：发现单个datafile恢复不
如整库恢复快！)sql alter database backup controlfile to
trace.shutdown immediate.exit 然后修改controlfile文件内容，去
掉不用的文件名 不完全恢复数据库：sqlplus / as
sysdbastartup nomount. 重建控制文件CREATE
CONTROLFILE REUSE DATABASE "XXX" RESETLOGS
ARCHIVELOGMAXLOGFILES 40MAXLOGMEMBERS
3MAXDATAFILES 400MAXINSTANCES 2MAXLOGHISTORY
454LOGFILEGROUP 1 (/oracle/oradata/xxx/rdb_redo01a) SIZE
10M,GROUP 2 (/oracle/oradata/xxx/rdb_redo02a) SIZE
10MDATAFILE
/oracle/oradata/xxx/system01.dbf,/oracle/oradata/xxx/undo01.dbf,
oracle/oradata/xxx/sysaux01.dbf,/oracle/oradata/xxx/pay_ts01.dbfC
HARACTER SET ZHS16GBK.recover database until cancel using
backup controlfile....alter database open resetlogs. 做数据恢复操
作：create table xxx as 0select xxx from xxx where xxx.exp,ftp
.dmp,imp 也可以如下所示，这样可以更简单一点：restore
database.recover database using backup controlfile until cancel.alter
database open resetlogs....END 100Test 下载频道开通，各类考试
题目直接下载。详细请访问 www.100test.com