Cisco CCNA (8)Cisco

71. Which layer is
responsible for providing mechanisms for multiplexing upper-layer
application, session establishment, and tear-down of virtual
circuits?A. Application B. Presentation C. Session D.
TransportAnswer D. 72. Which layer is responsible for coordinating
communication between systems?A. Application B. Presentation C.
Session D. PhysicalAnswer C. 73. Which layer is responsible for
negotiating data transfer syntax?A. application B. presentation C.
session D. transportAnswer B. 74. Which of the following is a
characteristic of a switch, but not of a repeater?A. Switches forward
packets based on the IPX or IP address in the frame.B. Switches
forward packets based only on the IP address in the packet. C.
Switches forward packets based on the IP address in the frame D.
Switches forward packets based on the MAC address in the
frameAnswer D. Switches are network device that filters, forwards,
and floods frames based on the destination address of each frame.
The switch operates at the data link layer of the OSI model. Switches
use layer 2 addresses to filter the network 75. How does the
cut-through switching technique work? A. The LAN switch copies
the entire frame into its buffers and then looks up the destination
address in its forwarding, table and determines the outgoing interface
B. The switch waits only for the header to be received before it
checks the destination address and starts forwarding the packets C.

By using broadcast addresses as source addresses D. By using a Class II repeater in a collision domain Answer B. Packet switching approach that streams data through a switch so that the leading edge of a packet exits the switch at the output port before the packet finishes entering the input port. A device using cut-through packet switching reads, processes, and forwards packets as soon as the destination address is looked up, and the outgoing port determined. Also known as on-the-fly packet switching. 76. How do switches use store and forward? A. The switch waits only for the header to be received before it checks the destination address and starts forwarding the packets B. The LAN switch copies the entire frame into its buffers and then looks up the 100Test