OracleDBA启动和关闭例程试选题Oracle认证考试 PDF转换可能丢失图片或格式,建议阅读原文

https://www.100test.com/kao_ti2020/618/2021_2022_OracleDBA_ E5_c102_618564.htm q. 1 : the database must be in this mode for the instance to be started 1. mount 2. open 3. nomount 4. none 3 q. 2 : when oracle startups up, what happens if a datafile or redo log file not available or corrupted due to o.s problems 1. oracle returns a warning message and opens the database 2. oracle returns a warning message and does not open the database 3. oracle returns a warning message and starts the database recovery 4. oracle ignores those files and functions normally 2 q. 3 : the restricted session system privilege should be given to 1. users, who need extra security while transfering the data between client and the server through sql*net or net8. 2. dbas, who perform structural maintenance exports and imports the data. 3. all of the above 4. none of the above 2 q. 4 : when starting up a database, if one or more of the files specified in the control_files parameter does not exist, or cannot be opened 1. oracle returns a warning message and does not mount the database 2. oracle returns a warning message and mounts the database 3. oracle ignores those files and functions normally 4. oracle returns a warning message and starts database recovery 1 q. 5 : bob tried to shutdown normal, oracle said it was unavailable, and when he tried to starup, oracle said that it was already started. what is the best mode that bob can use to force a shutdown on the server 1. normal 2. abort 3. immediate 4. none 2 q. 6 : tom issued a command to startup the database. what modes does the instance and database pass through to finally have the database

open 1. open, nomount, mount 2. nomount, mount, open 3. nomount, open, mount 4. mount, open, nomount 2 q. 7 : diane is a new dba and issued a shutdown command while her server is being used. after a while she figures that oracle is waiting for all the users to sign off. what shutdown mode did she use 1. normal 2. abort 3. immediate 4. none 1 q. 8 : which script file creates commonly used data dictionary views 1. sql.bsq 2. catalog.sql 3. utlmontr.sql 4. catproc.sql 2 q. 9 : in order to perform a full media recovery, the database must beshy. 1. mounted and opened using resetlog option 2. mounted but not opened 3. mounted and opened using archivelog option 4. you cannot perform a full media recovery 2 q. 10 : when is the parameter file read during startup 1. when opening the database 2. when mounting the database 3. during instance startup 4. in every stage 3 100Test 下载频道开通, 各类考试题目 直接下载。详细请访问 www.100test.com