

OracleDataGuard数据备份方案详解Oracle认证考试 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/644/2021_2022_OracleData_c102_644890.htm "libai"> Oracle DataGuard是一种数据库级别的HA方案，最主要功能是冗灾、数据保护、故障恢复等。在生产数据库的"事务一致性"时，使用生产库的物理全备份(或物理COPY)创建备库，备库会通过生产库传输过来的归档日志(或重做条目)自动维护备用数据库。将重做数据应用到备用库。本文介绍使用RMAN备份创建备库(dataguard).

一:Oracle DataGuard环境概述 1.软件环境 操作系统Red Linux Enterprise as 5 数据库版本Oracle 10g release 2 2.primary database IP:192.168.18.1 ORACLE_SID=db1 db_unique_name=db1

3.standby database IP:192.168.18.2 ORACLE_SID=standby db_unique_name=standby 二,主数据库(db1)做准备 1.设置主数据库为Force logging SQL> connect target sys/123456

RMAN> alter database create standby controlfile as
/oracle/rmanback/control01 6.配置listener.ora 和tnsnames.ora文件
启动listener.ora, [oracle@oracle dbs]\$ lsnrctl status LSNRCTL for
Linux: Version 10.2.0.4.0 - Production on 14-JUN-2009 02:54:29
Service "db1" has 1 instance(s). Instance "db1", status READY, has 1
handler(s) for this service... Service "db1_XPT" has 1 instance(s).

Instance "db1", status READY, has 1 handler(s) for this service... The
command completed successfully 配置tnsnames.ora vi
\$ORACLE_HOME/network/admin/tnsnames.ora db1 =
(DESCRIPTION = (ADDRESS_LIST = (ADDRESS =
(PROTOCOL = TCP)(HOST = 192.168.18.1)(PORT = 1521))))

```
(CONNECT_DATA = (SERVICE_NAME = db1) standby =  
(DESCRIPTION = (ADDRESS_LIST = (ADDRESS =  
(PROTOCOL = TCP)(HOST = 192.168.18.2)(PORT = 1521))) )  
(CONNECT_DATA = (SERVICE_NAME = standby) ) ) 100Test
```

下载频道开通，各类考试题目直接下载。详细请访问
www.100test.com