

squid透明代理配置过程:CentOSLinux认证考试 PDF转换可能丢失图片或格式，建议阅读原文

https://www.100test.com/kao_ti2020/644/2021_2022_squid_E9_80_8F_E6_98_c103_644726.htm [root@centos45 squid]# rpm -qa |grep squid squid-2.5.STABLE14-1.4E [root@centos45 squid]# service squid start 在未设置squid.conf状况下出现错误

"/var/spool/squid....." [root@centos45 squid]# vi squid.conf
http_port 3128 icp_prot 3130 cache_dir ufs /var/spool/squid 100 16 256 cache_access_log /var/log/squid/access.log cache_log /var/log/squid/cache.log cache_store_log /var/log/squid/store.log pid_filename /var/run/squid.pid #auth_param basic children 5 #auth_param basic realm Squid proxy-caching web server #auth_param basic credentialsttl 2 hours http_access allow all cache_effective_user squid cache_effective_group squid cache_mgr oice@126.com [root@centos45 etc]# su -l squid -c "/usr/sbin/squid -D" This account is currently not available. [root@centos45 etc]# ll /usr/sbin/squid -rwxr-xr-x 1 root root 654724 May 5 08:13

/usr/sbin/squid [root@centos45 etc]# /usr/sbin/squid -D 这一步虽然不能启动squid，但可以侦察错误，不检测DNS，有一定辅助作用 FATAL: Could not determine fully qualified hostname.

Please set visible_hostname 编辑特别推荐: Linux系统通过手机GPRS上网设置简介 提高Apache服务器性能四个建议 Linux认证能帮助你找到一份好工作吗 Squid Cache (Version 2.5.STABLE14): Terminated abnormally. CPU Usage: 0.028 seconds = 0.019 user 0.009 sys Maximum Resident Size: 0 KB Page faults with physical i/o: 0 Aborted [root@centos45 squid]# vi

```
/etc/squid/squid.conf visible_hostname feng-squid [root@centos45  
squid]# /usr/sbin/squid -D [root@centos45 squid]# netstat -tln |  
grep 312 [root@centos45 squid]# service squid start init_cache_dir  
/var/spool/squid... Starting squid: . [ OK ] [root@centos45 squid]#  
netstat -tln | grep 3128 tcp 0 0 0.0.0.0:3128 0.0.0.0:* LISTEN 100Test  
下载频道开通，各类考试题目直接下载。详细请访问  
www.100test.com
```